



EDGE

COLD WATER RANGE



Tomcat



Topcat



Leopard

Code	Model	operating pressure		delivery rate	absorbed power	rpm	voltage	max water temperature	weight with packaging	packaging	pieces for pallet	
		pag	bar	psi	l/min	W						RPM
2450	TOMCAT	12	130	1911	15	2600	2800	240~50	40	24.5/53.9	39x39 h 71	18(120-80)
2453	TOPCAT 9-130 ECO	13	130	1911	9	2800	2800	240~50	40	32/70.4	60x37,5 h 74	12(120x80)
2451	TOPCAT 11-100	13	120	1764	12	2800	1450	240~50	40	32/70.4	60x37,5 h 74	12(120x80)
2452	TOPCAT 9-130	13	140	2058	9	2800	1450	240~50	40	32/70.4	60x37,5 h 74	12(120x80)
1530	LEOPARD 12-100 STD	14	100	1500	12	-	-	240~50	60	43/94.6	86x40 h 87,5	-
2526	LEOPARD 10-130 AUTO	14	130	1911	10	-	-	240~50	60	43/94.6	86x40 h 87,5	-
2523	LEOPARD 12-100 AUTO	14	100	1500	12	-	-	240~50	60	43/94.6	86x40 h 87,5	-
1528	LEOPARD 15-150	14	150	2205	15	-	-	415~50	60	43/94.6	86x40 h 87,5	-
2524	LEOPARD 15-150 AUTO	14	150	2205	15	-	-	415~50	60	43/94.6	86x40 h 87,5	-
2460	POLECAT 11-120	15	120	1764	11	2800	1450	240~50	40	45/99	50x60 h 107	1
2461	POLECAT 15-150	16	150	2205	15	5000	1450	415~50	40	53/116.6	50x60 h 107	1
2462	POLECAT 15-200	16	200	2940	15	7000	1450	415~50	40	55/121	50x60 h 107	1
2470	MANX 12-100	17	110	1595	12	2800	1450	240~50	40	47/103.4	55x62 h 58	12(120x100)
2471	MANX 12-100	17	100	1500	12	2800	1450	110~50	40	47/103.4	55x62 h 58	12(120x100)
2472	MANX 15-150	17	150	2205	15	5000	1450	415~50	40	47/103.4	55x62 h 58	12(120x100)
2473	MANX 21-200	17	200	2940	21	9400	1450	415~50	40	55/121	55x62 h 58	12(120x100)
2480	JAGUAR 15-200	18	200	2940	15	7000	1450	415~50	40	84/184.8	85x64,5 h 100	1
2481	JAGUAR 21-200	18	200	2940	21	9400	1450	415~50	40	86/189.2	85x64,5 h 100	1



Polecat



Polecat



Manx



Jaguar