



EDGE

HOT WATER RANGE



Cub 10-130



Panther II ECO



Panther II HD



Tiger II

Code	Model	operating pressure		delivery rate	absorbed power	rpm	voltage	outlet temp.	fuel consumption	diesel tank		heat output	packaging	packaging weight	
		pag	bar							psi	l/min				W
2498	CUB 10-130	25	130	1911	10	2900	2800	240~50	max 90°	5,6	18 - 4.8	-	74	94x65x90	60 - 132
2499	PANTHER II 11-100 ECO	26	100	1470	11	3000	2800	240~50	max 140°	2,83	14 - 3.7	-	38	80x55x83	113-248.6
2500	PANTHER II 12-100 HD	27	120	1764	12	3000	1450	240~50	max 140°	4.7	18 - 4.8	-	58	94x65x90	124 - 272.8
2503	PANTHER II 9-130 HD	27	140	2058	9	3000	1450	240~50	max 140°	4.7	18 - 4.8	-	58	94x65x90	124 - 272.8
2504	PANTHER II 15-150 HD	27	150	2205	15	5500	1450	415~50	max 140°	5,7	18 - 4.8	-	74	94x65x90	135 - 297
2501	TIGER II 12-100 ECO	28	120	1764	12	3000	1450	240~50	max 140°	5,6	18 - 4.8	-	74	125x69x87	160 - 352
2507	TIGER II 12-100 HD	29	100	1470	12	5500	1450	240~50	max 140°	6.6	22 - 5.8	2.4-0.6	88	125x69x89	161 - 354.2
2505	TIGER II 12-100 HD	29	100	1470	12	5500	1450	110~50	max 140°	6.6	22 - 5.8	2.4-0.6	88	125x69x89	161 - 354.2
2502	TIGER II 15-200 HD	29	200	2940	15	7300	1450	415~50	max 140°	6.6	22 - 5.8	2.4-0.6	88	125x69x89	166 - 365.2
2506	TIGER II 21-200 HD	29	200	2940	21	9700	1450	415~50	max 140°	6.6	22 - 5.8	2.4-0.6	88	125x69x89	181 - 398.2
2606	WILDCAT 1012 ECO	30	100	1470	12	-	1450	240~50	max 140°	7	-	-	-	106x75x90	105 - 231
2605	WILDCAT 1012	30	100	1470	12	-	1450	240~50	max 140°	7	-	-	-	106x75x90	105 - 231
2600	WILDCAT 139	30	130	1911	9	-	1450	240~50	max 140°	7	-	-	-	106x75x90	105 - 231
2602	WILDCAT 1714	30	170	2499	14	-	-	415~50	max 140°	7	-	-	-	106x75x90	108 - 270,6
2025	TIGER 100/ 12HA 240V	31	100	1470	12	-	-	240~50	max 140°	7.5	30 - 8.1	-	-	111x77x80	150 - 330
2044	TIGER 100/12HA 110V	31	100	1470	12	-	-	110~50	max 140°	7.5	30 - 8.1	-	-	111x77x80	150 - 330
2040	TIGER 160/18HA 415V	31	160	2352	18	-	-	415~50	max 140°	8.5	30 - 8.1	-	-	111x77x80	180 - 396
2033	TIGER 200/21HA 415V	31	200	2940	21	-	-	415~50	max 115°	8.5	30 - 8.1	-	-	111x77x80	200 - 440
2508	VOLCANO	32	-	-	-	300	-	240~50	max 140°	5,6	18 - 4.8	-	74	94x65x90	60 - 132
12100	HOT STATIC 12-100	33	100	1470	12	3000	1450	240~50	max 140°	4.72	20 - 5.28	-	58	87,5x55x h 184	178 - 391,6
12300	HOT STATIC 15-200	33	200	2940	15	7300	1450	415~50	max 140°	4.72	20 - 5.28	-	58	87,5x55x h 184	178 - 391,6
12400	HOT STATIC 21-150	33	150	2205	21	7300	1450	415~50	max 140°	4.72	20 - 5.28	-	58	87,5x55x h 184	178 - 391,6



Tiger II HD



Wildcat Series



Tiger Series



Volcano Hot Box



Hot Static