

The small Kränzle quadro HP-cleaners:

kränzle®

Standard equipment:

- Integrated trolley
- 5 m power lead (12/150 TS T: 7,5 m)
- Cable reel
- Hose drum
- 15 m steel fabric high-pressure hose
- Water tank
- Spray gun with safety cut-out
- Dirtkiller lance with stainless steel pipe
- Flat jet lance with stainless steel pipe
- Total-Stop function
- Continuously adjustable pressure and quantity control
- Brass pump head
- Ceramic-coated pump plungers
- Dry-run safety
- Leakage return system
- Receptacle for spray gun with safety cut-out, spray lance and Dirtkiller
- Sucking in of detergents on the inlet side



Technical specifications

K 11/140 TS T

K 12/150 TS T

K 9/170 TS T

Operating pressure, continuously adjustable	10 - 140 bar	10 - 150 bar	10 - 170 bar
Max. admissible overpressure	155 bar	165 bar	190 bar
Water output at nominal pressure *1)	11 l/min.	12 l/min.	9 l/min.
Nozzle size (flat jet)	25045	25045	2503
Nozzle size Dirtkiller	045	045	030
Content water tank	7 l	7 l	7 l
Max. inlet water temperature into water tank	60 °C	60 °C	60 °C
Max. temperature for direct suction *2)	60 °C	60 °C	60 °C
Suction height for direct suction	2,5 m	2,5 m	2,5 m
Hose drum	yes	yes	yes
Dirtkiller	yes	yes	yes
Detergent sucking prior to pump	yes	yes	yes
Spraying of detergent under full pressure	yes	yes	yes
Total-Stop system	yes	yes	yes
Steel fabric high-pressure hose NW 6	15 m	15 m	15 m
Connected load	230 V ~, 14 A, 50 Hz	400 V, 6.8 A, 50 Hz	230 V ~, 14 A, 50 Hz
Motor speed	1,400 r.p.m.	1,400 r.p.m.	1,400 r.p.m.
Power input:	P 1 - 3.3 kW	P 1 - 3.5 kW	P 1 - 3.3 kW
Power output:	P 2 - 2.4 kW	P 2 - 2.8 kW	P 2 - 2.4 kW
Weight incl. accessories (empty water tank)	45 kg	45 kg	45 kg
Dimensions incl. handle, L x W x H in mm	590 x 360 x 850	590 x 360 x 850	590 x 360 x 850
Order No.	40.441 1	40.442 1	40.443 1

*1) Min. water quantity to be supplied to the high-pressure cleaner! *2) Direct suction is possible through by-passing of water tank!